

RINGS & FASTENERS

WIRE PROPERTIES

PHYSICAL PROPERTIES	VALUE	SPECIFICATION
Wire Diameter (mm)	3.0	As per manufacturer
Ring Dimension (Open) mm	38	As per manufacturer
Ring Dimension (Closed) mm	14	As per manufacturer

TENSILE STRENGTH

Galfan Coated Rings (MPa)	1520-1870	ASTM A641, ASTM A764, ASTM E8/MPT, ASTM B750
Stainless Steel Ring (MPa)	1520-1870	ASTM A313 Type 302 ASTM E8/MPT

COATING TYPES

Galfan Coated Rings	Galfan(95%Zinc +5% Aluminium Alloy + Mischmetals)				
Stainless Steel Rings	ASTM A313 Type 302, ASTM E8/MPT				

SUGGESTED RING QUANTITY

PRODUCT TYPE	GABIONS		ROCK MATTRESS		
Height (m)	1.0m with diaphragms	0.5m with diaphragms	0.17	0.23	0.30
No. per m ³	40-50	30-40	—	—	—
No. per m ²	—	—	15-18	15-18	15-20

DISTRIBUTORS OF :

- Geotextiles**
- Geogrids**
- Dewatering Tubes**
- Subsoil Drainage**
- Wick Drains**
- Erosion Control**
- Gabions & Rock Mattresses**
- Industrial Fabrics**
- Lining Systems**

DISCLAIMER : All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Global Synthetics Pty Ltd and Global Synthetics QLD Pty Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Global Synthetics Pty Ltd and Global Synthetics QLD Pty Ltd have a policy of continuous development so information and product specifications may change without notice.

