



# ProTac

## SELF ADHERING MEMBRANE STRIP / CULVERT BANDAGE

### DESCRIPTION

ProTac is a self adhering waterproofing membrane used in conjunction with resurfacing and overlaying operations and in pipe/culvert bandage operations to seal joints. It is comprised of a stress absorbing geotextile fabric that is combined with a rubberised bitumen to produce a composite membrane that bonds tenaciously to clean, dry surfaces.

### APPLICATIONS

Applications include crack sealing of many surfaces prior to surface overlaying or backfilling in applications such as:-

- Road surfaces
- Lane widening joints
- Other paved surfaces such as runways and carparks
- Bridge decks and pipe / culvert joint sealing
- Sealing of bridge girder joins prior to surfacing

### TYPICAL PROPERTIES

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE
Grab Tensile Strength	AS2001.2.3	N	900
Thickness	AS3706.1	mm	2.0
Mass Per Unit Area	AS3706.1	kg/m <sup>2</sup>	2.2
Dimensions		m	0.3 x 15.24

Other widths of ProTac available upon request.

DISTRIBUTORS OF :

- Geotextiles**
- Geogrids**
- Dewatering Tubes**
- Subsoil Drainage**
- Wick Drains**
- Erosion Control**
- Gabions & Rock Mattresses**
- Industrial Fabrics**
- Lining Systems**

DISCLAIMER : All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Global Synthetics Pty Ltd and Global Synthetics QLD Pty Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Global Synthetics Pty Ltd and Global Synthetics QLD Pty Ltd have a policy of continuous development so information and product specifications may change without notice.

